

G7L-1A-P-CB AC200/240 Information

Heisener.com Gistal Write Land Terr	 G7L-1A-P-CB AC200/240 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE SPST 20A 240V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7L-1A-P-CB AC200/240 Specifications

Manufacturer Part NumberG7L-1A-P-CB AC200/240ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysCategoryPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mAContact FormSPST-NO (1 Form A)Contact Rating (Current)SOVAC - MaxSwitching VoltageSOVAC - MaxTurn On Voltage (Max)SOVAC - MaxTurn Off Voltage (Max)SovaArease TimeSomsFeaturesSomsFeaturesInsulation-Class BMounting TypePC Pin		
CategoryRelaysPackage-PackageGTLSeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage50VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Max)36 VACOperate Time30msRelease TimeInsulation - Class BHounting TypeTurough Hole	Manufacturer Part Number	G7L-1A-P-CB AC200/240
PackagePower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn Off Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeTurough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease TimeSinsulation - Class BMounting TypeTurough Hole	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease TimeSinsulation - Class BMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Package	-
Coil TypeNon LachingCoil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Series	G7L
Coil Current10.2mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Coil Current	10.2mA
Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Coil Voltage	240VAC
Switching Voltage250VAC - MaxTurn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)150 VACTurn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Contact Rating (Current)	20A
Turn Off Voltage (Min)36 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Switching Voltage	250VAC - Max
Operate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Turn On Voltage (Max)	150 VAC
Release Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Turn Off Voltage (Min)	36 VAC
FeaturesInsulation - Class BMounting TypeThrough Hole	Operate Time	30ms
Mounting Type Through Hole	Release Time	30ms
	Features	Insulation - Class B
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G7L-1A-P-CB AC200/240 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-1A-P-CB AC200/240 Payment Methods





If you have any question about G7L-1A-P-CB AC200/240, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com