



G7L-1A-T-CB-AC12 Information

Heisener.com

Part Number G7L-1A-T-CB-AC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-1A-T-CB-AC12 Specifications

Manufacturer G7L-1A-T-CB-AC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Manufacturer Part Number	G7L-1A-T-CB-AC12
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	G7L
Coil Current Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 12VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Release Time Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Current	142mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Voltage	12VAC
Switching Voltage Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style 250VAC - Max 9 VAC 1.8 VAC 250VAC - Max 9 VAC 1.8 VAC 20ms 40ms 4	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 9 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Ouick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Max
Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	9 VAC
Release Time 30ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	1.8 VAC
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	30ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	30ms
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
Report criois:		Report errors?

G7L-1A-T-CB-AC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-1A-T-CB-AC12 Payment Methods



















G7L-1A-T-CB-AC12 Shipping Methods













If you have any question about G7L-1A-T-CB-AC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com