

G7L-1A-TUB-J-CB-AC24

G7L-1A-TUB-J-CB-AC24 Information



For Reference Only

Part Number G7L-1A-TUB-J-CB-AC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-1A-TUB-J-CB-AC24 Specifications

Manufacturer Part NumberG7L-1A-TUB-J-CB-AC24ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - Max
Category Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current T1mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Package - G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Coil TypeNon LatchingCoil Current71 mACoil Voltage24 VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30A
Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A
Contact Rating (Current) 30A
-
Switching Voltage 250VAC - Max
Turn On Voltage (Max) 18 VAC
Turn Off Voltage (Min) 3.6 VAC
Operate Time 30ms
Release Time 30ms
Features Insulation - Class B, Test Button
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)
Report errors?

G7L-1A-TUB-J-CB-AC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-1A-TUB-J-CB-AC24 Payment Methods



















G7L-1A-TUB-J-CB-AC24 Shipping Methods













If you have any question about G7L-1A-TUB-J-CB-AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com