

G7L-2A-B-J-CB-AC24

G7L-2A-B-J-CB-AC24 Information

4.4.4.4	Part Number	G7L-2A-B-J-CB-AC24
	Manufacturer	Omron Electronics Inc-EMC Div
A helsener.co	Category	Relays Power Relays, Over 2 Amps
V	Description	RELAY GEN PURPOSE DPST 25A 24V
	Package	-
-		For the pricing/inventory/lead time, please contact
		us
Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7L-2A-B-J-CB-AC24 Specifications

Manufacturer Part Number G7L-2A-B-J-CB-AC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage (Max) 18 VAC Turn On Voltage (Max) 3.6 VAC Querta Time 30ms Release Time Soms Features Insulation - Class B, Test Button Mauting Type Chasis Mount Termination Style Screw Terminal		
CategoryRelaysPackage-PackageGrSeriesGTRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil CurrentAVACContact FormDST (2 Form A)Contact Rating (Current)S0N CA C- MaxSwitching Voltage20VAC - MaxTurn On Voltage (Max)18 VACCurrent GurentSinsCurrent SeriesSonsRelease TimeSinsRelease TimeSins Cates ButtonFaturesCatsing Mounting TypeFormination StyleScew Terminal	Manufacturer Part Number	G7L-2A-B-J-CB-AC24
Power Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mAColl Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACOperate Time3.6 VACOperate Time30msRelease TimeSomsFeaturesInsulation - Class B, Test ButtonMounting TypeScrew Terminal	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACOperate Time3.6 VACRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChasis MountTermination StyleScrew Terminal	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease TimeJomsFeaturesInsulation - Class B, Test ButtonMounting TypeScew Terminal		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Package	-
Coil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease TimeInsulation - Class B, Test ButtonFeaturesInsulation - Class B, Test ButtonMounting TypeScrew Terminal	Series	G7L
Coil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Relay Type	General Purpose
Coil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Coil Type	Non Latching
Contact FormDPST (2 Form A)Contact Form25ASwitching (Current)250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountFermination StyleScrew Terminal	Coil Current	71mA
Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Coil Voltage	24VAC
Switching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Contact Rating (Current)	25A
Turn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Switching Voltage	250VAC - Max
Operate Time30msRelease Time30msFeatures30msMounting TypeInsulation - Class B, Test ButtonTermination StyleScrew Terminal	Turn On Voltage (Max)	18 VAC
Release Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Turn Off Voltage (Min)	3.6 VAC
FeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Operate Time	30ms
Mounting TypeChassis MountTermination StyleScrew Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	Insulation - Class B, Test Button
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7L-2A-B-J-CB-AC24 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

G7L-2A-B-J-CB-AC24 Payment Methods



G7L-2A-B-J-CB-AC24 Shipping Methods



If you have any question about G7L-2A-B-J-CB-AC24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com