

G7L-2A-BUB AC12

G7L-2A-BUB AC12 Information

Heisener.com	 G7L-2A-BUB AC12 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE DPST 25A 12V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7L-2A-BUB AC12 Specifications

Manufacturer Part Number G7L-2A-BUB AC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Acting (Current) 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 250VAC - Max Switching Voltage (Max) 9VAC Turn On Voltage (Max) 18 VAC Operate Time 30ms Release Time - Features - Features - Features -		
CategoryRelaysPackage-PackageGrSeriesGTRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mACoil Actor12VACContact FormDST (2 Form A)Contact Rating (Current)25ASwitching Voltage20VAC - MaxTurn ON Voltage (Max)9 VACCurrent3.8 VACSprace Time30msRelease Time-Fatures-Mounting TypeCasis MountTermination StyleScew Terminal	Manufacturer Part Number	G7L-2A-BUB AC12
PackagePower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mAColl CurrentDPST (2 Form A)Contact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage (Max)9 VACTurn On Voltage (Max)9 VACOperate Time30msRelease Time-Fatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACOperate Time30msRelease Time-Features-Mounting TypeChasis MountTermination StyleScrew Terminal	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage9 VACTurn On Voltage (Max)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage9 VACTurn On Voltage (Max)9 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleSrew Terminal	Package	-
Coil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACOperate Time30msRelease Time-Features-Mounting TypeChassis MountTermination StyleScrew Terminal	Series	G7L
Coil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Relay Type	General Purpose
Coil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Coil Type	Non Latching
Contact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Coil Current	142mA
Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Coil Voltage	12VAC
Switching Voltage250VAC - MaxTurn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)9 VACTurn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Termination	Contact Rating (Current)	25A
Turn Off Voltage (Min)1.8 VACOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Switching Voltage	250VAC - Max
Operate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	9 VAC
Release Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Turn Off Voltage (Min)	1.8 VAC
Features-Mounting TypeChassis MountTermination StyleScrew Terminal	Operate Time	30ms
Mounting TypeChassis MountTermination StyleScrew Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	-
•	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7L-2A-BUB AC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-2A-BUB AC12 Payment Methods



G7L-2A-BUB AC12 Shipping Methods



If you have any question about G7L-2A-BUB AC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com