



G7L-2A-P-CB-AC24 Information



For Reference Only

Part Number G7L-2A-P-CB-AC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 20A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-2A-P-CB-AC24 Specifications

ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G7L-2A-P-CB-AC24
Package - GTL Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Release Time 1 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin	Series	G7L
Coil Current Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Coil Current	71mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style	Coil Voltage	24VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style 7 PC Pin	Switching Voltage	250VAC - Max
Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VAC
Release Time 30ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	3.6 VAC
Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin	Operate Time	30ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	30ms
Termination Style PC Pin	Features	Insulation - Class B
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G7L-2A-P-CB-AC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-2A-P-CB-AC24 Payment Methods



















G7L-2A-P-CB-AC24 Shipping Methods













If you have any question about G7L-2A-P-CB-AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com