



#### **G7L-2A-P-CB-DC24 Information**



For Reference Only

Part Number G7L-2A-P-CB-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 20A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G7L-2A-P-CB-DC24 Specifications**

Manufacturer Category Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 79mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Omver Relays Relay Series Relay Series Relay Series Rower Relays, Over 2 Amps Power Relays Powe		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current79mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30ms	Manufacturer Part Number	G7L-2A-P-CB-DC24
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 79mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage Max) 18 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time Series G7L Series G7L General Purpose General Purpose Von Latching General Purpose 109 Non Latching 109 No	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 79mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 3250VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 330ms	Category	Relays
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 79mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 79mA  Coil Voltage 24VDC  Contact Form DPST (2 Form A)  Contact Rating (Current) 20A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Package	-
Coil TypeNon LatchingCoil Current79mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30ms	Series	G7L
Coil Current 79mA  Coil Voltage 24VDC  Contact Form DPST (2 Form A)  Contact Rating (Current) 20A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Relay Type	General Purpose
Coil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30ms	Coil Type	Non Latching
Contact Form DPST (2 Form A)  Contact Rating (Current) 20A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Coil Current	79mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  30ms	Coil Voltage	24VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  30ms	Contact Rating (Current)	20A
Turn Off Voltage (Min)  Operate Time  3.6 VDC  30ms	Switching Voltage	250VAC - Max
Operate Time 30ms	Turn On Voltage (Max)	18 VDC
	Turn Off Voltage (Min)	3.6 VDC
D. 1	Operate Time	30ms
Release Time 30ms	Release Time	30ms
Features Insulation - Class B	Features	Insulation - Class B
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **G7L-2A-P-CB-DC24** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G7L-2A-P-CB-DC24 Payment Methods



















## **G7L-2A-P-CB-DC24** Shipping Methods













If you have any question about G7L-2A-P-CB-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com