



G7L-2A-P-CB DC48 Information

Heisener.com

Part Number G7L-2A-P-CB DC48

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 20A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-2A-P-CB DC48 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage48VDCContact FormDPST (2 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time30msFeaturesInsulation - Class BMounting TypeThrough Hole	Manufacturer Part Number	G7L-2A-P-CB DC48
Package Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type G7L General Purpose G7L General Purpose G7L Amps G7L	Manufacturer	Omron Electronics Inc-EMC Div
Package - G7L Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Category	Relays
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Release Time 1 30ms Features Insulation - Class B Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Release Time 1 30ms Features Insulation - Class B Mounting Type Through Hole	Series	G7L
Coil Current 40mA Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Release Time 1 30ms Features Insulation - Class B Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Coil Current	40mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type 20A	Coil Voltage	48VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Switching Voltage	250VAC - Max
Operate Time 30ms Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Turn On Voltage (Max)	36 VDC
Release Time 30ms Features Insulation - Class B Mounting Type Through Hole	Turn Off Voltage (Min)	7.2 VDC
Features Insulation - Class B Mounting Type Through Hole	Operate Time	30ms
Mounting Type Through Hole	Release Time	30ms
	Features	Insulation - Class B
Termination Style PC Pin	Mounting Type	Through Hole
Termination Style	Termination Style	PC Pin
Report errors?		Report errors?

G7L-2A-P-CB DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-2A-P-CB DC48 Payment Methods



















G7L-2A-P-CB DC48 Shipping Methods













If you have any question about G7L-2A-P-CB DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com