

G7L-2A-TUB-J-CB-AC12

G7L-2A-TUB-J-CB-AC12 Information



For Reference Only

Part Number G7L-2A-TUB-J-CB-AC12

Manufacturer Omron Electronics Inc-EMC Div

S. B. I

Category Relays
Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 25A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-2A-TUB-J-CB-AC12 Specifications

Manufacturer Part Number Manufacturer Manufacturer Category Relays Power Relays, Over 2 Amps Package Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 250VAC - Max
Category Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current)
Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Package - G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Relay Type General Purpose Coil Type Non Latching Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Coil TypeNon LatchingCoil Current142mACoil Voltage12VACContact FormDPST (2 Form A)Contact Rating (Current)25A
Coil Current 142mA Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Coil Voltage 12VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Contact Form DPST (2 Form A) Contact Rating (Current) 25A
Contact Rating (Current) 25A
Switching Voltage 250VAC - Max
Turn On Voltage (Max) 9 VAC
Turn Off Voltage (Min) 1.8 VAC
Operate Time 30ms
Release Time 30ms
Features Insulation - Class B, Test Button
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)
Report errors

G7L-2A-TUB-J-CB-AC12 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-2A-TUB-J-CB-AC12 Payment Methods



















G7L-2A-TUB-J-CB-AC12 Shipping Methods













If you have any question about G7L-2A-TUB-J-CB-AC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com