

Heisener.com

G7L-2A-TUBJ-80-CB AC24

G7L-2A-TUBJ-80-CB AC24 Information

Part Number G7L-2A-TUBJ-80-CB AC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 25A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7L-2A-TUBJ-80-CB AC24 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time Jonate House (Mas) Insulation - Class B, Test Button Mounting Type Chassis Mount		
CategoryRelaysPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test Button	Manufacturer Part Number	G7L-2A-TUBJ-80-CB AC24
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Manufacturer	Omron Electronics Inc-EMC Div
Package - G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test Button		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Package	-
Coil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test Button	Series	G7L
Coil Current 71mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Relay Type	General Purpose
Coil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test Button	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Coil Current	71mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Coil Voltage	24VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Contact Rating (Current)	25A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button	Switching Voltage	250VAC - Max
Operate Time30msRelease Time30msFeaturesInsulation - Class B, Test Button	Turn On Voltage (Max)	18 VAC
Release Time 30ms Features Insulation - Class B, Test Button	Turn Off Voltage (Min)	3.6 VAC
Features Insulation - Class B, Test Button	Operate Time	30ms
	Release Time	30ms
Mounting Type Chassis Mount	Features	Insulation - Class B, Test Button
~ · · ·	Mounting Type	Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)	Termination Style	Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

G7L-2A-TUBJ-80-CB AC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-2A-TUBJ-80-CB AC24 Payment Methods



















G7L-2A-TUBJ-80-CB AC24 Shipping Methods













If you have any question about G7L-2A-TUBJ-80-CB AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com