



### **G7SA-3A1B DC48 Information**

Part Number G7SA-3A1B DC48

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

**Description** RELAY SAFETY 4PST 6A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G7SA-3A1B DC48 Specifications**

Manufacturer Part NumberG7SA-3AIB DC48ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesG7SARelay TypeSafetyCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeSocketableTermination StylePlug In		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	G7SA-3A1B DC48
Package-SeriesG7SARelay TypeSafetyCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         G7SA           Relay Type         Safety           Coil Type         Non Latching           Coil Current         7.5mA           Coil Voltage         48VDC           Contact Form         4PST (3 Form A, 1 Form B)           Contact Rating (Current)         6A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         36 VDC           Turn Off Voltage (Min)         4.8 VDC           Operate Time         20ms           Release Time         10ms           Features         Sealed - Flux Protection           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesG7SARelay TypeSafetyCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type Safety Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Socketable Termination Style Plug In	Package	-
Coil Type Non Latching Coil Current 7.5mA  Coil Voltage 48VDC  Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 6A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 36 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Socketable  Termination Style Plug In	Series	G7SA
Coil Current Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Socketable Termination Style	Relay Type	Safety
Coil Voltage 48VDC  Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 6A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 36 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Socketable  Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 6A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 36 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Socketable  Termination Style Plug In	Coil Current	7.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  36 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  20ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Socketable Termination Style Plug In	Contact Form	4PST (3 Form A, 1 Form B)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  20ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	6A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	36 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	4.8 VDC
Features Sealed - Flux Protection  Mounting Type Socketable  Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	10ms
Termination Style Plug In	Features	Sealed - Flux Protection
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### **G7SA-3A1B DC48 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G7SA-3A1B DC48 Payment Methods**



















# **G7SA-3A1B DC48 Shipping Methods**













If you have any question about G7SA-3A1B DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com