

Heisener.com

# **G8P-1114P-BI-US-DC24**

### G8P-1114P-BI-US-DC24 Information

Part Number G8P-1114P-BI-US-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 30A 24V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G8P-1114P-BI-US-DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Power Relays, Over 2 Amps  Package  - Series  G8P  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  36mA  Coil Voltage  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  Switching Voltage  250VAC, 28VDC - Max
Category Relays Power Relays, Over 2 Amps Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max
Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max
Package - G8P  Relay Type General Purpose  Coil Type Non Latching  Coil Current 36mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC, 28VDC - Max
Series G8P  Relay Type General Purpose  Coil Type Non Latching  Coil Current 36mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC, 28VDC - Max
Relay Type General Purpose  Coil Type Non Latching  Coil Current 36mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC, 28VDC - Max
Coil Type Non Latching  Coil Current 36mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC, 28VDC - Max
Coil Current 36mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC, 28VDC - Max
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Contact Rating (Current)  Switching Voltage  30A  250VAC, 28VDC - Max
Switching Voltage 250VAC, 28VDC - Max
TO NATIONAL AND ADDRESS OF THE PROPERTY OF THE
Turn On Voltage (Max) 18 VDC
Turn Off Voltage (Min) 2.4 VDC
Operate Time 15ms
Release Time 10ms
Features Sealed - Fully
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

#### **G8P-1114P-BI-US-DC24 Guarantees**



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G8P-1114P-BI-US-DC24 Payment Methods



















## **G8P-1114P-BI-US-DC24 Shipping Methods**













If you have any question about G8P-1114P-BI-US-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com