



G8P-1A2T-F DC12 Information



For Reference Only

Part Number G8P-1A2T-F DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G8P-1A2T-F DC12 Specifications

Manufacturer Part NumberG8P-1A2T-F DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current77mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)9 VDC
Category Relays Power Relays, Over 2 Amps Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max
Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max
Package - G8P Relay Type General Purpose Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Coil Type Non Latching Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Coil Current 77mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Contact Rating (Current) 30A Switching Voltage 250VAC, 28VDC - Max
Switching Voltage 250VAC, 28VDC - Max
Turn On Voltage (Max) 9 VDC
Turn Off Voltage (Min) 1.2 VDC
Operate Time 15ms
Release Time 10ms
Features Insulation - Class F
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.187"/0.250"
Report errors?

G8P-1A2T-F DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G8P-1A2T-F DC12 Payment Methods



















G8P-1A2T-F DC12 Shipping Methods













If you have any question about G8P-1A2T-F DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com