



G8P-1C4P-AS DC24 Information

Heisener.com

Part Number G8P-1C4P-AS DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G8P-1C4P-AS DC24 Specifications

Manufacturer Part Number G8P-IC4P-AS DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
Category Relays Power Relays, Over 2 Amps Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	G8P-1C4P-AS DC24
Package-SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current36mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G8P
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	36mA
Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style 250VAC, 28VDC - Max 18 VDC 15ms 15ms 15ms 10ms Features Insulation - Class F, Sealed - Fully PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 28VDC - Max
Operate Time 15ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G8P-1C4P-AS DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G8P-1C4P-AS DC24 Payment Methods

































If you have any question about G8P-1C4P-AS DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com