



G8P-1CP DC110 Information

Heisener.com

Part Number G8P-1CP DC110

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 110V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G8P-1CP DC110 Specifications

Manufacturer Part Number G8P-ICP DC110 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 9mA Coil Voltage 110VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9mACoil Voltage110VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class FMounting TypeThrough Hole	Manufacturer Part Number	G8P-1CP DC110
Package - Series G8P Relay Type General Purpose Coil Type Non Latching Coil Current 9mA Coil Voltage 110VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9mACoil Voltage110VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class FMounting TypeThrough Hole	Category	Relays
SeriesG8PRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9mACoil Voltage110VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class FMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9mA Coil Voltage 110VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 9mA Coil Voltage 110VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Series	G8P
Coil Current 9mA Coil Voltage 110VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage110VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time15msRelease Time10msFeaturesInsulation - Class FMounting TypeThrough Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Coil Current	9mA
Contact Rating (Current) Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type 10A	Coil Voltage	110VDC
Switching Voltage 250VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Switching Voltage	250VAC, 28VDC - Max
Operate Time 15ms Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Turn On Voltage (Max)	82.5 VDC
Release Time 10ms Features Insulation - Class F Mounting Type Through Hole	Turn Off Voltage (Min)	11 VDC
Features Insulation - Class F Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	10ms
	Features	Insulation - Class F
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G8P-1CP DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G8P-1CP DC110 Payment Methods



















G8P-1CP DC110 Shipping Methods













If you have any question about G8P-1CP DC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com