

# G8W-1C6T-R-DC12

# **G8W-1C6T-R-DC12 Information**



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# G8W-1C6T-R-DC12 Specifications

ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG8WRelay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil CurrentSPDT (1 Form C)Contact FormSVDCContact Rating (Current)SVDCSwitching Voltage16VDC - MaxSurton Type10VDCContact Form10VDCContact Rating (Current)SVDCSwitching Voltage (Max)1 VDCSurton Type10NSRelease TimeJomsFeaturesReistorMunting TypeSocketable		
CategoryRelaysPackage-PackageG8WRelay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8VDCSwitching Voltage16VDC - MaxTurn On Voltage (Max)8VDCTurn Off Voltage (Min)1VDCSpeare Time10msRelase TimeIomsFeaturesReistorMounting TypeSockatabeTermination StyleHug In	Manufacturer Part Number	G8W-1C6T-R-DC12
Power Relays, Over 2 AmpsPackage-SeriesG8WRelay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil Voltage12 VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage16 VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePug In	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG8WRelay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage (Max)8 VDC - MaxTurn On Voltage (Max)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePug In	Category	Relays
SeriesG8WRelay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCOperate Time20msRelease Time10msFeaturesReistorMounting TypeSocketableTermination StylePug In		Power Relays, Over 2 Amps
Relay TypeAutomotiveCoil TypeNon LatchingCoil Current-Coil VoltageI2VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching VoltageI6VDC - MaxTurn On Voltage (Max)8 VDCOperate Time20msRelease TimeI0msFeaturesResistorMounting TypeSocketableTermination StyleHug In	Package	-
Coil TypeNon LachingCoil Current-Coil VoltageI2VDCContact FormSPDT (1 Form C)Contact Rating (Current)OASwitching VoltageI6VDC - MaxTurn On Voltage (Max)8 VDCCurrent FineI2VDCRelease TimeOmsFeaturesIomsFeaturesSeckataleMounting TypeSockataleTermination StyleHug In	Series	G8W
Coil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Relay Type	Automotive
Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePing In	Coil Type	Non Latching
Contact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Coil Current	-
Contact Rating (Current)20ASwitching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Coil Voltage	12VDC
Switching Voltage16VDC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)8 VDCTurn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Contact Rating (Current)	20A
Turn Off Voltage (Min)1 VDCOperate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Switching Voltage	16VDC - Max
Operate Time20msRelease Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	8 VDC
Release Time10msFeaturesResistorMounting TypeSocketableTermination StylePlug In	Turn Off Voltage (Min)	1 VDC
FeaturesResistorMounting TypeSocketableTermination StylePlug In	Operate Time	20ms
Mounting TypeSocketableTermination StylePlug In	Release Time	10ms
Termination Style Plug In	Features	Resistor
· · · · · · · · · · · · · · · · · · ·	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### G8W-1C6T-R-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# G8W-1C6T-R-DC12 Payment Methods



# **G8W-1C6T-R-DC12** Shipping Methods



If you have any question about G8W-1C6T-R-DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com