

G9EC-1 DC12 Information



For Reference Only

Part Number G9EC-1 DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 200A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G9EC-1 DC12 Specifications

Manufacturer Part Number G9EC-1 DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G9EC-1 Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms Features Sealed - Fully		
Category Relays Power Relays, Over 2 Amps Package - Series G9EC-1 Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Manufacturer Part Number	G9EC-1 DC12
Package - Series G9EC-1 Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G9EC-1 Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Category	Relays
Series G9EC-1 Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Package	-
Coil Type Non Latching Coil Current 938mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Series	G9EC-1
Coil Current938mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)200ASwitching Voltage400VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.96 VDCOperate Time50msRelease Time30ms	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 200A Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Coil Current	938mA
Contact Rating (Current) Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Coil Voltage	12VDC
Switching Voltage 400VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.96 VDC Operate Time 50ms Release Time 30ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Soms Release Time 30ms	Contact Rating (Current)	200A
Turn Off Voltage (Min) Operate Time 50ms Release Time 30ms	Switching Voltage	400VDC - Max
Operate Time 50ms Release Time 30ms	Turn On Voltage (Max)	9 VDC
Release Time 30ms	Turn Off Voltage (Min)	0.96 VDC
	Operate Time	50ms
Features Sealed - Fully	Release Time	30ms
ļ · · · · · · · · · · · · · · · · · · ·	Features	Sealed - Fully
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Termination Style Wire Leads	Termination Style	Wire Leads
Report errors?		Report errors?

G9EC-1 DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G9EC-1 DC12 Payment Methods



















G9EC-1 DC12 Shipping Methods













If you have any question about G9EC-1 DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com