

GA-14 Information



For Reference Only

Part Number GA-14

Manufacturer TDK Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 1700PF 10KV Z5T BUTTON

Package Button

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GA-14 Specifications

Manufacturer Part Number GA-14 Manufacturer TDK Corporation Category Capacitors Package Button Series GA Capacitance 1700pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package Button Series GA Capacitance 1700pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	GA-14
Package Button Series GA Capacitance 1700pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	TDK Corporation
Package Button Series GA Capacitance 1700pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series GA Capacitance 1700pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance1700pFTolerance±10%Voltage - Rated10000V (10kV)Temperature CoefficientZ5TOperating Temperature10°C ~ 85°CFeaturesHigh Voltage, Low Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRequires HolderPackage / CaseButtonSize / Dimension1.575" Dia x 0.630" L (40.00mm x 16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package	Button
Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient Z5T Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	GA
Voltage - Rated10000V (10kV)Temperature CoefficientZ5TOperating Temperature10°C ~ 85°CFeaturesHigh Voltage, Low Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRequires HolderPackage / CaseButtonSize / Dimension1.575" Dia x 0.630" L (40.00mm x 16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	1700pF
Temperature Coefficient Operating Temperature 10°C ~ 85°C Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) Lead Spacing Lead Style - Lead Style	Tolerance	±10%
Operating Temperature10°C ~ 85°CFeaturesHigh Voltage, Low Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRequires HolderPackage / CaseButtonSize / Dimension1.575" Dia x 0.630" L (40.00mm x 16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	10000V (10kV)
Features High Voltage, Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - High Voltage, Low Dissipation Factor Requires Holder - Low Dissipation Factor - High Voltage, Low Dissipation Factor - High Voltage, Low Dissipation Factor - High Voltage, Low Dissipation Factor - Lead Spacing - Lead Style	Temperature Coefficient	Z5T
Ratings - General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Max - Lead Style	Operating Temperature	10°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Features	High Voltage, Low Dissipation Factor
Failure Rate - Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Requires Holder Package / Case Button Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	General Purpose
Package / CaseButtonSize / Dimension1.575" Dia x 0.630" L (40.00mm x 16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 1.575" Dia x 0.630" L (40.00mm x 16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Requires Holder
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Button
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	1.575" Dia x 0.630" L (40.00mm x 16.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

GA-14 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GA-14 Payment Methods



















GA-14 Shipping Methods













If you have any question about GA-14, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com