



### **GBB100DYRD Information**

Heisener.com

Part Number GBB100DYRD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 200POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **GBB100DYRD Specifications**

Manufacturer Part Number         GBB100DYRD           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         100           Number of Positions         200           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish Thickness         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	•		
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         100           Number of Positions         200           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	GBB100DYRD	
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         100           Number of Positions         200           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         Black           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         100           Number of Positions         200           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         Black           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects	
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         100           Number of Positions         200           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row $100$ Number of Positions $200$ Card Thickness $0.062"$ ( $1.57mm$ )Number of Rows $2$ Pitch $0.050"$ ( $1.27mm$ )FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in ( $0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, $0.125"$ ( $3.18mm$ ) DiaOperating Temperature $-65°$ C $\sim 125°$ C	Series	-	
Number of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	100	
Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	200	
Pitch 0.050" (1.27mm)  Features Card Extender  Mounting Type Board Edge, Straddle Mount  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) DiaOperating Temperature $-65^{\circ}$ C ~ $125^{\circ}$ C	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ 125°C	Features	Card Extender	
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Mounting Type	Board Edge, Straddle Mount	
Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Termination	Solder	
Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Contact Material	Phosphor Bronze	
Contact Type Cantilever  Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **GBB100DYRD** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **GBB100DYRD Payment Methods**



















### **GBB100DYRD Shipping Methods**













If you have any question about GBB100DYRD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com