



GBB105DHND Information

Heisener.com

Part Number GBB105DHND

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 210POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GBB105DHND Specifications

Manufacturer Part Number GBB105DHND Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 105 Number of Positions 210 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	GEETICE III (E Specifications		
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 105 Number of Positions 210 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	GBB105DHND	
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 105 Number of Positions 210 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 105 Number of Positions	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row105Number of Positions210Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row105Number of Positions210Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row105Number of Positions210Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row105Number of Positions210Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 210 Card Thickness $0.062"$ (1.57mm)Number of Rows 2 Pitch $0.050"$ (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 10μ in (0.25 μ m)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	105	
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Positions	210	
Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 125 °C	Features	-	
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65° C $\sim 125^{\circ}$ C	Termination	Solder	
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Contact Material	Phosphor Bronze	
Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors	Operating Temperature	-65°C ~ 125°C	
Report errors			Report errors?

GBB105DHND Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GBB105DHND Payment Methods



















GBB105DHND Shipping Methods













If you have any question about GBB105DHND, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com