

GBB75DYHR

GBB75DYHR Information

Heisener.com	Part Number Manufacturer Category Description Package	GBB75DYHR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 150POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GBB75DYHR Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions0.062" (1.57mm)Number of Rows2Picth0.050" (1.27mm)Number of Rows2PicturesBoard LockMounting TypeSolder, StaggeredContact FinishGoldContact Finish Thickness0.062Contact Finish Thickness0.012 (1.57mm)Contact TypeGoldContact Finish ThicknessSolder, StaggeredContact StringSolder, StaggeredContact TypeGultiverContact TypeGultiverContact Finish ThicknessJunin 0.25µm)Contact TypeGultiverFange FeatureJencectorFange FeatureSolder, StaggeredContact StaggeredSolder, StaggeredContact TypeGultiverContact Finish ThicknessSolder, StaggeredContact StaggeredSolder, Staggered	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeGaldContact TypeSolder, StaggeredContact TypeSolder StaggeredContact TypeGaldContact TypeGaldContact TypeSolder, StaggeredContact TypeGaldContact TypeGaldContact TypeCantileverContact TypeSolder, StaggeredContact Type<	Manufacturer Part Number	GBB75DYHR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact Finish ThicknessSolder, StaggeredContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish ThicknessGoldContact Finish ThicknessInpin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSolder, StaggeredContact MaterialGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 150 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness Iopin (0.25µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	75
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	150
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeI0µin (0.25µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperatures-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Features	Board Lock
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

GBB75DYHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GBB75DYHR Payment Methods



GBB75DYHR Shipping Methods



If you have any question about GBB75DYHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com