

**GBB85DYFT Information**


For Reference Only

**Part Number** [GBB85DYFT](#)  
**Manufacturer** Sullins Connector Solutions  
**Category** Connectors, Interconnects  
[Card Edge Connectors - Edgeboard Connectors](#)  
**Description** CONN EDGE DUAL FEMALE 170POS .050  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**GBB85DYFT Specifications**

Manufacturer Part Number	<a href="#">GBB85DYFT</a>
Manufacturer	Sullins Connector Solutions
Category	Connectors, Interconnects <a href="#">Card Edge Connectors - Edgeboard Connectors</a>
Package	-
Series	-
Card Type	Non Specified - Dual Edge
Gender	Female
Number of Positions/Bay/Row	85
Number of Positions	170
Card Thickness	0.062" (1.57mm)
Number of Rows	2
Pitch	0.050" (1.27mm)
Features	-
Mounting Type	Surface Mount
Termination	Solder
Contact Material	Phosphor Bronze
Contact Finish	Gold
Contact Finish Thickness	10µin (0.25µm)
Contact Type	Cantilever
Color	Black
Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40
Operating Temperature	-65°C ~ 125°C

[Report errors?](#)

## GBB85DYFT Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## GBB85DYFT Payment Methods



## GBB85DYFT Shipping Methods



If you have any question about GBB85DYFT, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)