

GBC30DCMI

GBC30DCMI Information

Contraction for the second sec	Part Number Manufacturer Category Description Package	GBC30DCMI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 60POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GBC30DCMI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Number of Rows-Features-Mounting TypeThrough HoleContact MaterialOidContact Finish ThicknessGoldContact Finish ThicknessIopin (0.25µm)Contact TypeHairpin BellowsContact TypeBlackFaquere FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialWire WrapContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact TypeBlackFaquereTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer Part Number	GBC30DCMI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact Type10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-5°°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialPhosphor BronzeContact Finish Thickness10/µin (0.25µm)Contact TypeHairpin BellowsContact Type10/µin 0.25µm)Contact TypeHairpin BellowsFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeHairpin BellowsContact TypeGoldContact TypeHairpin BellowsColorBlackFlange Feature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialWire WrapContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFage Feature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact FinishGoldContact TypeIpi (0.25µm)Contact TypeIpi (0.25µm)ColorBlackFalaresFor Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-or Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Gold Contact Finish Thickness Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-65°C ~ 125°C	Number of Positions/Bay/Row	30
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	60
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Wire Wrap
Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

GBC30DCMI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GBC30DCMI Payment Methods



GBC30DCMI Shipping Methods



If you have any question about GBC30DCMI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com