

GBM12DCWH

est a Quote

GBM12DCWH Information

Heisener.com	Part Number	GBM12DCWH	
	Manufacturer	Sullins Connector Solutions	Γ
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	Ģ
	Description	CONN EDGE DUAL FMALE 24POS 0.156	Ē
	Package	-	
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GBM12DCWH Specifications

ManufacturerSullins Connector SolutionsCardege ConnectorsConnectors, Edgeboard ConnectorsPackage-Package-Stries-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions0.602° (1.57mm)Number of Rows0.602° (1.57mm)Number of Rows0.156° (3.96mm)Features-Mounting TypeNonghe HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact TypeHaipin BellowsContact TypeBackFaquere FeatureSolderContact TypeGoldContact TypeGoldContact TypeGoldContact TypeSolerContact Finish ThicknessJujin (0.25µm)Contact TypeGoldContact TypeSolerContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeSolerContact TypeGoldContact	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions/Bay/Row0.602° (1.57mm)Number of Rows0.602° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeForough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIpin BellowsContact TypeBackFaquere FeatureToroy Mountopening, Unthreaded, 0.125° (3.18mm) DiaColorBackFaquere Toroy-Contact TypeGold Contact Sing Mountopening, Unthreaded, 0.125° (3.18mm) DiaColorBackFaquere Toroy-Contact TypeGold Contact Sing Mountopening, Unthreaded, 0.125° (3.18mm) DiaContact Type-Contact Type <td>Manufacturer Part Number</td> <td colspan="2">GBM12DCWH</td>	Manufacturer Part Number	GBM12DCWH	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature- 50°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature- Sol% c~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact Finish Thickness0.0d2Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFaquere-5°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-55°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	12	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	24	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
		Report errors?	

GBM12DCWH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GBM12DCWH Payment Methods



GBM12DCWH Shipping Methods



If you have any question about GBM12DCWH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com