

GBM15DCCT

GBM15DCCT Information

Heisener.com	Part Number Manufacturer Category Description Package	GBM15DCCT Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 30POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GBM15DCCT Specifications

ManufacturerSullins Connector SolutionsCadegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFinogh Hole, Right AngleContact FinishSolderContact Finish Thickness0.062" (1.57mm)Contact Finish ThicknessGoldContact TypeMongh Hole, Right AngleContact Finish ThicknessSolderContact TypeInjun (0.25µm)Contact TypeBackFlange FeatureFlang Hole, Negen (J. Ster, 4.40)	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness0.0d2Contact TypeInjun (0.25µm)Contact TypeInjun (0.25µm)Contact TypeBackFaques FeaturesSolderContact TypeHairpin BellowsContact TypeBackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer Part Number	GBM15DCCT	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-5°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeHoip IngellowsContact TypeHairpin BellowsColorBlackFlange Feature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeHairpin BellowsColorBlackFlange Feature-S0°C ~ 125°C	Series	-	
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Type10µin (0.25µm)ColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 30 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Mounting Type Solder Contact Material Gold Contact Finish Gold Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	15	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	30	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

GBM15DCCT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GBM15DCCT Payment Methods



GBM15DCCT Shipping Methods



If you have any question about GBM15DCCT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com