

GBM31DCWH

est a Quote

GBM31DCWH Information

Heisener.com	Part Number	GBM31DCWH	
	Manufacturer	Sullins Connector Solutions	- 6
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	- 3
	Description	CONN EDGE DUAL FMALE 62POS 0.156	<u> </u>
	Package	-	
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	I

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GBM31DCWH Specifications

Manufacturer Part Number GBM31DCWH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Card Edge Connectors - Edgeboard Connectors Package - Stries - Card Type Non Specified - Dual Edge Gender Non Specified - Dual Edge Number of Positions/Bay/Row 31 Number of Positions/Bay/Row 62 Number of Positions 0.62° (1.57mm) Number of Rows 2 Pich 0.156° (3.96mm) Yeatures - Mounting Type Solder Tornight Hole Solder Contact Marcial Solder Contact Finish Thickness Gold Contact Finish Thickness Iopin Osport Color Back Color Back Faugr Feature Toy Mout Opening, Unthreaded, 0.125° (3.18mm) Dia Color Back			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions/Bay/Row62Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Nongh HoleContact MaterialNoghor BronzeContact MaterialGoldContact Finish ThicknessGoldContact TypeHaipin BellowsContact TypeBackFaquere EductionSinder Contact MaterialContact TypeGoldContact TypeGol	Manufacturer Part Number	GBM31DCWH	
ActageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Oudper of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type50/derContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBackFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFolderContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.5µm)Contact TypeHairpin BellowsColorBlackFlange Feature- Solor 215°COperating Temperature- Sol°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness0.0d2Contact Finish Thickness10µin (0.25µm)Contact TypeHairin BellowsColorBlackFlange Feature-5°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeBackColorBackFaqueresConduct Openaing, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange Feature-5°C ~ 125°C	Series	-	
Number of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-Mounting TypeSolderContact MaterialSolderContact Finish Thickness0µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-Contact Sector-Contact Sector-Color- <td< td=""><td>Number of Positions/Bay/Row</td><td>31</td></td<>	Number of Positions/Bay/Row	31	
Number of Rows2Nich0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	62	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$	
		Report errors?	

GBM31DCWH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GBM31DCWH Payment Methods



GBM31DCWH Shipping Methods



If you have any question about GBM31DCWH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com