

# **GBM36DTAT**

### **GBM36DTAT Information**

Heisener.com	Part Number Manufacturer Category Description Package	GBM36DTAT Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 72POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GBM36DTAT Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions/Bay/Row0602" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFinogh Hole, Right AngleContact ThinknessSolderContact Finish ThicknessGoldContact Finish ThicknessIopin (0.25µm)Contact TypeLoop BellowsContact TypeLoop BellowsContact TypeBackFaque FeatureSolderContact TypeIndin (0.25µm)Contact TypeIopin BellowsContact TypeSolderContact TypeFeaturesContact TypeSolderContact Type <t< th=""><th>_</th><th></th><th></th></t<>	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsContact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer Part Number	GBM36DTAT	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange Feature-S°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBalckFlange FeatureFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeIopin BionzeContact TypeLoop BellowsColarBiackFage FeatureFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeLoop BellowsColorBackFlange Feature-S0°C ~ 125°C	Series	-	
Number of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeIop BellowsColorBackFauresFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 72   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Cortact Material Solder   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Color Black   Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	36	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	72	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Openating Temperatures-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **GBM36DTAT Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GBM36DTAT Payment Methods**



## **GBM36DTAT** Shipping Methods



If you have any question about GBM36DTAT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com