

## **GCC19DRTH**

uest a Quote

## **GCC19DRTH Information**

Heisener.com	Part Number	GCC19DRTH	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 38POS 0.100	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GCC19DRTH Specifications**

Manufacturer Part Number GCC19DRTH   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Package -   Stries -   Gard Type Mon Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 19   Number of Positions/Bay/Row 38   Card Thickness 0.062° (1.57mm)   Number of Rows 2   Pitch 0.100° (2.54mm)   Young Hole Solder   Young Hole Solder   Contact Material Solder   Young Hole Solder   Contact Finish Thickness Gold   Contact Finish Thickness Solymon Forser   Contact Finish Thickness Solidor Solum   Color Black   Flange Feature S				
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nongh HoleContact FinishSolderContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeFull BellowsContact TypeSulper Solution Solu	Manufacturer Part Number	GCC19DRTH		
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type19Trongh HoleContact MaterialSolderContact FinishGoldContact Finish Thickness3uin (0.76µm)Contact TypeHellellowsContact TypeSolderContact TypeSolderContact TypeSolderContact TypeGoldContact TypeGul BellowsColorBackFaquerecontacton Contact, SolderColorSolder	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessJupin (0.76µm)Contact TypeFull BellowsColorBackFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects		
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessGoldContact TypeFull BellowsColorBackFaqueres-Forp Foatures-ColorBickContact Type Foature-ColorSolderCo		Card Edge Connectors - Edgeboard Connectors		
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSupin (0.76µm)Contact TypeHull BellowsColorBackFange Feature-Operating Temperature-Sol C ~ 125°C-	Package	-		
GenderFemaleNumber of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationSolderContact Material9hosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange Feature-co Nourt Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-6°C ~ 125°C	Series	-		
Number of Positions/Bay/Row19Number of Positions38Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Mounting TypeSolderContact MaterialSolderContact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBackFange Feature-Solger Contact SpectrumSolder Contact SpectrumColorSolder Contact Spectr	Card Type	Non Specified - Dual Edge		
Number of Positions 38   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Gold   Contact Finish Thickness 30µin (0.76µm)   Contact Type Full Bellows   Color Black   Flange Feature - GovC ~ 125°C	Gender	Female		
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeSull BellowsColorBackFlange FeatureContact OpenationOperating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	19		
Number of Rows2Number of Rows0.100" (2.54mm)Features-Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-5°C ~ 125°C	Number of Positions	38		
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeSulpin (0.76µm)ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C~125°C	Card Thickness	0.062" (1.57mm)		
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJujin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Number of Rows	2		
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)		
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-		
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole		
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder		
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze		
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold		
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)		
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows		
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black		
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		
Report errors?	Operating Temperature	-65°C ~ 125°C		
			Report errors?	

#### **GCC19DRTH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE UARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GCC19DRTH Payment Methods**





If you have any question about GCC19DRTH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com