

# GCC35DRTF-S13

est a Quote

## **GCC35DRTF-S13 Information**

Heisener.com	Part Number	GCC35DRTF-S13	
	Manufacturer	Sullins Connector Solutions	- 6
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	Ř
	Description	CONN EDGE DUAL FMALE 70POS 0.100	5
	Package	-	
		For the pricing/inventory/lead time, please contact	l
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## GCC35DRTF-S13 Specifications

Manufacturer Part NumberGCC35DRTF-S13ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard Edge, Stradle MountMounting TypeBoard Edge, Stradle MountContact HairialGoldContact Finish Thickness30µin (0.76µm)Contact TypeBuakContact TypeBuakContact TypeBuakContact TypeGoldContact TypeBuakContact TypeBuakColorBlack			
CategoryConnectors, InterconnectsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGoald Edge, Straddle MountFeaturesSolderMounting TypeSolderContact KniefsGoldContact FinishGoldContact FinishGoldContact TypeSupportFontact TypeSolderContact TypeSolderContact TypeSupportContact FinishSupportContact TypeSupportContact TypeSupportContact SupportSupportContact Support<	Manufacturer Part Number	GCC35DRTF-S13	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions0062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard Edge, Straddle MountFeaturesSolderContact MaterialPhosphor BronzeContact FinishGoldContact FinishGoldContact TypeBiak	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact FinishSipin 0.76µm)Contact TypeHul BellowsColorBack	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialOldoContact Finish ThicknessGoldContact TypeBiakColorBlack	Package	-	
GenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Series	-	
Number of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Card Type	Non Specified - Dual Edge	
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeBul BellowsColorBlack	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeBlack	Number of Positions/Bay/Row	35	
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Number of Positions	70	
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Features	Card Extender	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Mounting Type	Board Edge, Straddle Mount	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Termination	Solder	
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlack	Contact Material	Phosphor Bronze	
Contact Type Full Bellows   Color Black	Contact Finish	Gold	
Color Black	Contact Finish Thickness	30µin (0.76µm)	
	Contact Type	Full Bellows	
Elange Feature Top Mount Opening Floating Bobbin 0 116" (2.95mm) Dia	Color	Black	
Top Mount Opening, Troating Dobbin, 0.110 (2.95min) Dia	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-65°C ~ 125°C	
Report errors		Report errors	

### **GCC35DRTF-S13** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### GCC35DRTF-S13 Payment Methods





If you have any question about GCC35DRTF-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com