

GCC44DREF-S13

est a Quote

GCC44DREF-S13 Information

| Heisener.com | Part Number | GCC44DREF-S13 |
|--------------------|--------------|---|
| | Manufacturer | Sullins Connector Solutions |
| | Category | Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors |
| | Description | CONN EDGE DUAL FMALE 88POS 0.100 |
| | Package | - |
| | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GCC44DREF-S13 Specifications

| ManufacturerSullins Connector SolutionsCardegoryConnectors, InterconnectsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row88Card Tyick0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)FeaturesGoald Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact FinishSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeFeal BellowsContact TypeFull BellowsContact TypeSider Scallen Scalle | | | | |
|---|-----------------------------|---|----------------|--|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Colar Erinish ThicknessSupin (0.76µm)Colar Erinish ThicknessSupin (0.76µm)ColorBackFlange FeatureConton Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperatures6° < 125°C | Manufacturer Part Number | GCC44DREF-S13 | | |
| Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Reaures Card Edge, Straddle Mount Solder Eyelet(s) Solder Eyelet(s) Contact Material Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Back Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C | Manufacturer | Sullins Connector Solutions | | |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Category | Connectors, Interconnects | | |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-5°C ~ 125°C | | Card Edge Connectors - Edgeboard Connectors | | |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsColorBackFage FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Package | - | | |
| GenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact TypeGoldContact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Series | - | | |
| Number of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Card Type | Non Specified - Dual Edge | | |
| Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Gender | Female | | |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Number of Positions/Bay/Row | 44 | | |
| Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureCop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Number of Positions | 88 | | |
| Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Card Thickness | 0.062" (1.57mm) | | |
| FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Number of Rows | 2 | | |
| Mounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Pitch | 0.100" (2.54mm) | | |
| TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Features | Card Extender | | |
| Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Mounting Type | Board Edge, Straddle Mount | | |
| Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Termination | Solder Eyelet(s) | | |
| Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Contact Material | Phosphor Bronze | | |
| Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Contact Finish | Gold | | |
| ColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Contact Finish Thickness | 30µin (0.76µm) | | |
| Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C | Contact Type | Full Bellows | | |
| Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$ | Color | Black | | |
| | Flange Feature | Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia | | |
| Report errors? | Operating Temperature | -65°C ~ 125°C | | |
| | | | Report errors? | |

GCC44DREF-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GCC44DREF-S13 Payment Methods





If you have any question about GCC44DREF-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com