

GCM10DRKN-S13

uest a Quote

GCM10DRKN-S13 Information

Heisener.com	Part Number	GCM10DRKN-S13
	Manufacturer	Sullins Connector Solutions
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
	Description	CONN EDGE DUAL FMALE 20POS 0.156
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us W l i l l i l i l i
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GCM10DRKN-S13 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2PitchOard Edge, Straddle MountFeaturesGolderMounting TypeBoard Edge, Straddle MountContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessSilpien Silpien Si	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSudactColorBlackFlange Feature-<	Manufacturer Part Number	GCM10DRKN-S13
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlage Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeFeallewsContact TypeBlackColart TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderColart TypeSolderCol		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBackFauge Feature-Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact TypeGuld SupportContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBackFange Feature-Operating Temperature50°C ~ 125°C	Series	-
Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Thickness Gold Contact Type Full Bellows Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	10
Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	20
Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessSoluin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperatures-55°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

GCM10DRKN-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GCM10DRKN-S13 Payment Methods





If you have any question about GCM10DRKN-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com