

# **GCM28DRES**

est a Quote

## **GCM28DRES** Information

| Heisener.com       | Part Number  | GCM28DRES   |   |
|--------------------|--------------|---|---|
|                    | Manufacturer | Sullins Connector Solutions   |   |
|                    | Category     | Connectors, Interconnects<br>Card Edge Connectors - Edgeboard Connectors  | 3 |
|                    | Description  | CONN EDGE DUAL FMALE 56POS 0.156  |   |
|                    | Package      | -   |   |
|                    |              | For the pricing/inventory/lead time, please contact                       |   |
| For Reference Only |              | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com | R |

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **GCM28DRES** Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions/Bay/Row56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsContact TypeSuld Solder Sold |                             |   |  |
|---|-----------------------------|---|--|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeMendendumGolder Evelet(s)Solder Eyelet(s)Contact MaterialOigu (0.76µm)Contact Finish ThicknessGoldContact TypeFell BellowsContact TypeSider Sectors)Contact TypeGide Sectors)Contact TypeGoldContact TypeSider Sectors)Contact TypeSider Sectors)Contact TypeSider Sectors)Cortact TypeSider Sec   | Manufacturer Part Number    | GCM28DRES   |  |
| Card Edge Connectors - Edgeboard Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 28   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Peatures -   Mounting Type Panel Mount   Posphor Bronze -   Contact Material Solder Eyelet(s)   Contact Finish Thickness Gold   Contact Type Full Bellows   Color Full Bellows   Color Back   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  | Manufacturer                | Sullins Connector Solutions                         |  |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Card Thickness0.662" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGuju (0.76µm)Contact TypeFull BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperaturesi68" C ~ 125°C   | Category                    | Connectors, Interconnects                           |  |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  |                             | Card Edge Connectors - Edgeboard Connectors         |  |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Package                     | -   |  |
| GenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Series                      | -   |  |
| Number of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBiackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C   | Card Type                   | Non Specified - Dual Edge                           |  |
| Number of Positions 56   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Gold   Contact Finish Gold   Contact Finish Thickness 30µin (0.76µm)   Color Black   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C   | Gender                      | Female  |  |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Number of Positions/Bay/Row | 28  |  |
| Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Number of Positions         | 56  |  |
| Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Card Thickness              | 0.062" (1.57mm)                                     |  |
| Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Number of Rows              | 2   |  |
| Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Pitch                       | 0.156" (3.96mm)                                     |  |
| TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Features                    | -   |  |
| Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Mounting Type               | Panel Mount   |  |
| Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Termination                 | Solder Eyelet(s)                                    |  |
| Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Material            | Phosphor Bronze                                     |  |
| Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Finish              | Gold  |  |
| ColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Finish Thickness    | 30μin (0.76μm)                                      |  |
| Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Type                | Full Bellows  |  |
| Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$  | Color                       | Black   |  |
|   | Flange Feature              | Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia |  |
| Report errors?  | Operating Temperature       | $-65^{\circ}C \sim 125^{\circ}C$                    |  |
|   |                             | Report errors?                                      |  |

#### **GCM28DRES** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GCM28DRES** Payment Methods





If you have any question about GCM28DRES, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com