

# **GEC13DREH**

#### **GEC13DREH Information**

| Heisener.com<br>Ottal lerves card ter | Part Number<br>Manufacturer<br>Category<br>Description<br>Package | GEC13DREH<br>Sullins Connector Solutions<br>Connectors, Interconnects<br>Card Edge Connectors - Edgeboard Connectors<br>CONN EDGE DUAL FMALE 26POS 0.100<br>-<br>For the pricing/inventory/lead time, please contact |                 |
|---------------------------------------|---|--|-----------------|
| For Reference Only                    |   | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GEC13DREH Specifications**

| Manufacturer Part Number GEC13DREH   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Package Card Edge Connectors - Edgeboard Connectors   Package -   Stries -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 3   Number of Positions/Bay/Row 3   Number of Positions/Bay/Row 26   Striks 0.062°''.157mm)   Yumber of Rows 2   Pactures .   Mounting Type 9and Mount   Young Type Panel Mount   Young Type Posphore Brows   Contact Finish Solder Eyelet(s)   Contact Finish Thickness Fin   Contact Finish Thickness Fin   Contact Finish Thickness Fin   Color Back   Faugreeature Full Bellows   Color Back   Color Back   Color Solution Solor Solution   Solar Solution Solor Solution   Color Back   Color Solution Solor Solution   Solution Solution Solor Solution Solution   Color Solution Solution   | _                           |  |
|--|-----------------------------|--|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Number of Rows0.100" (2.54mm)Features-Nonting TypePanel MountContact MaterialNospor BronzeContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeSulder SecureContact Finish Thickness100µin (2.54µm)Contact TypeSulder SecureContact TypeSulder SecureCont   | Manufacturer Part Number    | GEC13DREH  |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish100µí (2.54µm)Contact FinishTinContact Finish Thickness100µí (2.54µm)Contact Finish Thickness100µí (2.54µm)Contact TypeHalellowsContact Finish Thickness10µún (2.54µm)Contar TypeSolder Eyelet(s)Contact Type10µún (2.54µm)Contact TypeSolder Eyelet(s)Contact TypeSolder SellowsContact TypeSolder Sellows <tr< td=""><td>Manufacturer</td><td>Sullins Connector Solutions</td></tr<> | Manufacturer                | Sullins Connector Solutions                        |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Card Thickness0.62" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish100µin (2.54µm)Contact Finish Thickness10µin (2.54µm)Contact Finish Thickness10µin (2.54µm)Contact TypeHalellowsContact Type10µin (2.54µm)ColorHalellowsColorFall BellowsFalage Feature0p Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C   | Category                    | Connectors, Interconnects                          |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness10µin (2.54µm)Contact TypeHallellowsContact TypeSolder Selet(s)Contact Type10µin (2.54µm)Contact TypeHallellowsContact TypeSolder Selet(s)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  |                             | Card Edge Connectors - Edgeboard Connectors        |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBackFlange FeatureCop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Package                     | -  |
| GenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeHul BellowsColorBlackFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C   | Series                      | -  |
| Number of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOnde MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeHallellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C   | Card Type                   | Non Specified - Dual Edge                          |
| Number of Positions     26       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.100" (2.54mm)       Features     -       Mounting Type     Panel Mount       Termination     Solder Eyelet(s)       Contact Material     Phosphor Bronze       Contact Finish     Tin       Contact Type     Full Bellows       Color     Black       Flange Feature     Coperating Temperature   | Gender                      | Female   |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBackFlange FeatureCopy Contact Sing TemperatureOperating Temperature65° C ~ 125°C   | Number of Positions/Bay/Row | 13   |
| Number of Rows2Nich0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange Feature-5°C ~ 125°C  | Number of Positions         | 26   |
| Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C  | Card Thickness              | 0.062" (1.57mm)                                    |
| Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Number of Rows              | 2  |
| Mounting TypePanel MountMounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Pitch                       | 0.100" (2.54mm)                                    |
| TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Features                    | -  |
| Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Mounting Type               | Panel Mount  |
| Contact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Termination                 | Solder Eyelet(s)                                   |
| Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Contact Material            | Phosphor Bronze                                    |
| Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Finish              | Tin  |
| ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Finish Thickness    | 100µin (2.54µm)                                    |
| Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Contact Type                | Full Bellows                                       |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$   | Color                       | Black  |
|  | Flange Feature              | Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia |
| Report errors?   | Operating Temperature       | $-65^{\circ}C \sim 125^{\circ}C$                   |
|  |                             | Report errors?                                     |

#### **GEC13DREH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GEC13DREH Payment Methods**



### **GEC13DREH Shipping Methods**



If you have any question about GEC13DREH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com