

GEC15DTEH

GEC15DTEH Information

Heisener.com	 GEC15DTEH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 30POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GEC15DTEH Specifications

Manufacturer Part Number GEC 15DTEH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Package - Stries - Gend Foge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Stries - Gender Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 15 Number of Positions 30 Gat Thickness 0.062° (1.57mm) Number of Rows 2 Pitch 0.100° (2.54mm) Mounting Type Pael Mount Young Type Pael Mount Gontart Material Solder Eyelet(s) Contact Finish Thickness Inin Contact Finish Thickness Finip Costant Contact Finish Thickness Finip Costant Gontact Type Back Color Back FalageFeature Toy MountOpening, Unthreaded, 0.125° (3.18mm) Dia <		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Nounting Type9and MountFeatures-Contact MaterialNospor BronzeContact FinishSider Eyels(s)Contact Finish Thickness100µin (2.54µm)Contact Finish ThicknessFull BellowsContact TypeSulde Scalum)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact Finish ThicknessSider Scalum)Contact TypeSulde Scalum)Contact TypeSider Scalum	Manufacturer Part Number	GEC15DTEH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Ourder of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish100µin (2.54µm)Contact Finish Thickness10µin (2.54µm)Contact TypeHalellowsContact TypeHosphor BronzeContact TypeSolder Eyelet(s)Contact TypeHalellowsContact TypeSolder SequenceColorBlackFaquereTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeFull BellowsColorBackFinage Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact Finish ThicknessFull BellowsColorBackFlange FeatureCop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-55°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Series	-
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBackFlange Feature-Operating Temperature-Solver Colors-Solver Colors <t< td=""><td>Card Type</td><td>Non Specified - Dual Edge</td></t<>	Card Type	Non Specified - Dual Edge
Number of Positions 30 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Tin Contact Type Full Bellows Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBackFlange FeatureCopy Contact Solution (2.52°C)	Number of Positions/Bay/Row	15
Number of Rows2Number of Rows0.100" (2.54mm)Features-Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	30
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypePanel MountHountSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Panel Mount
Contact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)
Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Tin
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	100µin (2.54µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

GEC15DTEH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GEC15DTEH Payment Methods



GEC15DTEH Shipping Methods



If you have any question about GEC15DTEH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com