

GEC40DRYI

GEC40DRYI Information

Heisener.com	Part Number Manufacturer Category Description Package	GEC40DRYI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 80POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GEC40DRYI Specifications

ManufacturerSullins Connector SolutionsCardegeroyConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions0.062" (1.57mm)Number of Rows2Pictures-Number of Rows2Pictures-Mounting TypeNongen HoleContact FinishSolderContact Finish Thickness100µí (2.54µm)Contact Finish Thickness100µí (2.54µm)Contact TypeHolesContact TypeHolesContact TypeSolderContact TypeSolder </th <th>_</th> <th></th>	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeSudarContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeSolderContact TypeSudarContact TypeSudar<	Manufacturer Part Number	GEC40DRYI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness100µin (2.54µm)Contact Finish Thickness10µin (2.54µm)Contact TypeFull BellowsContact Type50lderContact Type50µin (2.54µm)Contact Type50µin (2.54µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Material9hosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact Type5ulderContact TypeFull BellowsContact TypeFull BellowsFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions/Bay/Row80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessSolderContact Finish Thickness100µin (2.54µm)Contact TypeFeal HolesContact Finish Thickness100µin (2.54µm)Contact Finish ThicknessFeal HolesContact TypeFeal HolesContact TypeFeal HolesContact TypeFeal HolesContact TypeFeal HolesContact TypeFeal HolesContact TypeFeal HolesColorBlackFlange FeatureCop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishTinContact TypeFull BellowsColorBlackFlarge FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorFull BellowsFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Finish Thickness Full Bellows Color Black Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange Feature-50°C ~ 125°C	Number of Positions/Bay/Row	40
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange Feature-55°C ~ 125°C	Number of Positions	80
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100μin (2.54μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Tin
Color Black Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	100µin (2.54µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors

GEC40DRYI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GEC40DRYI Payment Methods



GEC40DRYI Shipping Methods



If you have any question about GEC40DRYI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com