

GEM25DRYF

est a Quote

GEM25DRYF Information

Heisener.com	Part Number	GEM25DRYF	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	ξ
	Description	CONN EDGE DUAL FMALE 50POS 0.156	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GEM25DRYF Specifications

Manufacturer Part NumberGEM25DRYFManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type50Contact Finish0.156" (3.96mm)Contact Finish50Contact Finish50Contact Finish100pin (2.54µm)Contact FinishFenaleContact FinishFiniContact Type60derFinish Thickness100pin (2.54µm)Contact TypeFull BellowsColorBlackFining Temperature50% C ~ 125°C				
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting Type50Features-Nongh Gabardian156° (3.96mm)Fortures-Mounting Type-Order AtterialSolderContact FinishSolderContact Finish100 (1.554m)Contact TypeInil BellowsColorBackFinage Feature50 (2.54mm) Edge)Finage Feature50 (2.54mm) Edge) <td>Manufacturer Part Number</td> <td colspan="2">GEM25DRYF</td>	Manufacturer Part Number	GEM25DRYF		
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type50Contact MaterialSolderContact FinishSolderContact FinishTinContact Finish100 (1.54µm)Contact TypeHallellowsColorBackFinage FeatureSolderFinage FeatureTony Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldyn Carden SolderContact Finish100µin (2.54µm)Contact TypeFul BellowsColorBackFinage FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Category	Connectors, Interconnects		
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish100µi (2.54µm)Contact Finish Thickness100µi (2.54µm)ColorBlackFlange FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		Card Edge Connectors - Edgeboard Connectors		
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeNon Specified PoleYonder AffertianSolderContact MaterialOndyn BronzeContact FinishTinContact FinishThickness0.0ju (0.54µm)Contact TypeBialelowsFange FeaturesSolderFange FeaturesSolderContact SpecifiesTinContact TypeSolderFinishThicknessSolderFinishThicknessSolderFange FeatureSolderFinishThicknestSolderSol	Package	-		
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialPosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeBalckFange FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Series	-		
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness100µin (2.54µm)Contact TypeHul BellowsContact TypeSulderFalures100µin (2.54µm)Fange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Type	Non Specified - Dual Edge		
Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Gender	Female		
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish100µin (2.54µm)Contact TypeFul BellowsColorBlackFange FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions/Bay/Row	25		
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFul BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions	50		
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Thickness	0.062" (1.57mm)		
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Rows	2		
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95µm) Dia	Pitch	0.156" (3.96mm)		
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Features	-		
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Mounting Type	Through Hole		
Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Termination	Solder		
Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Material	Phosphor Bronze		
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish	Tin		
ColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish Thickness	100µin (2.54µm)		
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Type	Full Bellows		
	Color	Black		
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		
	Operating Temperature	-65°C ~ 125°C		
Report en			Report errors?	

GEM25DRYF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GEM25DRYF Payment Methods



GEM25DRYF Shipping Methods



If you have any question about GEM25DRYF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com