



## **GEM25DTAI Information**

Heisener.com

Part Number GEM25DTAI

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 50POS 0.156

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **GEM25DTAI Specifications**

| Manufacturer Part NumberGEM25DTAIManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features- |                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Category  Connectors, Interconnects  Card Edge Connectors - Edgeboard Connectors  Package  - Series  - Card Type  Non Specified - Dual Edge  Gender  Female  Number of Positions/Bay/Row  25  Number of Positions  50  Card Thickness  0.062" (1.57mm)  Number of Rows  Pitch  0.156" (3.96mm)  Features  -                                  |                |
| Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features -                                                                                     |                |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features -                                                                                                                                  |                |
| Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features -                                                                                                                                            |                |
| Card Type  Gender  Female  Number of Positions/Bay/Row  25  Number of Positions  50  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.156" (3.96mm)  Features                                                                                                                                                                    |                |
| GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-                                                                                                                                                                                                      |                |
| Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-                                                                                                                                                                                                                  |                |
| Number of Positions         50           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -                                                                                                                                                      |                |
| Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -                                                                                                                                                                                               |                |
| Number of Rows         2           Pitch         0.156" (3.96mm)           Features         -                                                                                                                                                                                                                                                |                |
| Pitch         0.156" (3.96mm)           Features         -                                                                                                                                                                                                                                                                                   |                |
| Features -                                                                                                                                                                                                                                                                                                                                   |                |
|                                                                                                                                                                                                                                                                                                                                              |                |
|                                                                                                                                                                                                                                                                                                                                              |                |
| Mounting Type Through Hole, Right Angle                                                                                                                                                                                                                                                                                                      |                |
| Termination Solder                                                                                                                                                                                                                                                                                                                           |                |
| Contact Material Phosphor Bronze                                                                                                                                                                                                                                                                                                             |                |
| Contact Finish Tin                                                                                                                                                                                                                                                                                                                           |                |
| Contact Finish Thickness 100µin (2.54µm)                                                                                                                                                                                                                                                                                                     |                |
| Contact Type Loop Bellows                                                                                                                                                                                                                                                                                                                    |                |
| Color Black                                                                                                                                                                                                                                                                                                                                  |                |
| Flange Feature Top Mount Opening, Threaded Insert, 4-40                                                                                                                                                                                                                                                                                      |                |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$                                                                                                                                                                                                                                                                         |                |
|                                                                                                                                                                                                                                                                                                                                              | Report errors? |

#### **GEM25DTAI** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GEM25DTAI Payment Methods**



















## **GEM25DTAI Shipping Methods**













If you have any question about GEM25DTAI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com