



### **GHA500F-15-SNF Information**



For Reference Only

**Part Number** GHA500F-15-SNF **Manufacturer** Cosel USA, Inc.

**Category** Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** 3X5 SWITCHING POWER SUPPLIES 501

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **GHA500F-15-SNF Specifications**

Manufacturer Part Number         GHA500F-15-SNF           Manufacturer         Cosel USA, Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         GHA           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         GHA           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Manufacturer Part Number	GHA500F-15-SNF
Package         -           Series         GHA           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Manufacturer	Cosel USA, Inc.
Package         -           Series         GHA           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         GHA           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         33.4A           Power (Watts)         501W           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Package	-
Number of Outputs  Voltage - Input  90 ~ 264 VAC  Voltage - Output 1  15V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Apower (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Size / Dimension  1	Series	GHA
Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)33.4APower (Watts)501WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-20°C ~ 80°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Туре	Enclosed
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Voltage - Isolation Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Size / Dimension  15V  - Overating Temperature	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output 2  - Output 3  - Current - Output (Max)  - Commercial), Medical  - Woltage - Isolation  4kV (4000V)  - Commercial), Medical  - Commercial), Medical  - Woltage - Isolation  4kV (4000V)  - Commercial), Medical  - Commercial), Medical  - Voltage - Isolation  - Voltage - Isolation  - Voltage - Isolation  - Commercial), Medical  - Voltage - Isolation  - Voltage - I	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Current - Output (Max)  - Current - Output (Max)  - Commercial), Medical  4kV (4000V)  - Commercial), Medical  - Current - Output (Max)  - Current - Output (Max)	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max)  33.4A  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 2	-
Current - Output (Max)  33.4A  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 3	-
Power (Watts) 501W  Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 4	-
Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Current - Output (Max)	33.4A
Voltage - Isolation 4kV (4000V)  Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Power (Watts)	501W
Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Applications	ITE (Commercial), Medical
Operating Temperature  -20°C ~ 80°C (With Derating)  Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  Chassis Mount  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, DC Input Capable, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Efficiency	91%
Mounting Type Chassis Mount Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Operating Temperature	-20°C ~ 80°C (With Derating)
Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)
		Report errors?

#### **GHA500F-15-SNF Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GHA500F-15-SNF Payment Methods**



















## **GHA500F-15-SNF Shipping Methods**













If you have any question about GHA500F-15-SNF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com