

### **GHA500F-15-T3 Information**



For Reference Only

**Part Number** GHA500F-15-T3 **Manufacturer** Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC PS (OPEN FRAME)

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **GHA500F-15-T3 Specifications**

Manufacturer Part Number         GHA500F-15-T3           Manufacturer         Cosel USA, Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         GHA           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         GHA           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Manufacturer Part Number	GHA500F-15-T3	
Package         -           Series         GHA           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Manufacturer	Cosel USA, Inc.	
Package         -           Series         GHA           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         GHA           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)		AC DC Converters	
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W (500W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         91%           Operating Temperature         -20°C ~ 80°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Package	-	
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)150W (500W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-20°C ~ 80°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Series	GHA	
Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)150W (500W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-20°C ~ 80°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Туре	Open Frame	
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Size / Dimension  15V  15V  15V  15V  15V  15V  15V  10A  10A  10A  10A  10A  10B  10B  10B	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Size / Dimension  -20°C L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Coutput Air	Voltage - Output 1	15V	
Voltage - Output 4  Current - Output (Max)  10A  Power (Watts)  150W (500W Forced Air)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 2	-	
Current - Output (Max)  Power (Watts)  150W (500W Forced Air)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  91%  Operating Temperature  -20°C ~ 80°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  150W (500W Forced Air)  4kV (4000V)  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Current - Output (Max)	10A	
Voltage - Isolation 4kV (4000V)  Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Power (Watts)	150W (500W Forced Air)	
Efficiency 91%  Operating Temperature -20°C ~ 80°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Applications	ITE (Commercial), Medical	
Operating Temperature  -20°C ~ 80°C (With Derating)  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Voltage - Isolation	4kV (4000V)	
Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Efficiency	91%	
Mounting Type Chassis Mount Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Operating Temperature	-20°C ~ 80°C (With Derating)	
Size / Dimension 6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	6.50" L x 3.35" W x 1.61" H (165.3mm x 85.2mm x 41.0mm)	
			Report errors?

#### **GHA500F-15-T3 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GHA500F-15-T3 Payment Methods**



















## **GHA500F-15-T3 Shipping Methods**













If you have any question about GHA500F-15-T3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com