

GIB1404-E3/81

GIB1404-E3/81 Information

www.horsener.com	Part Number Manufacturer Category Description Package	GIB1404-E3/81 Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE GEN PURP 200V 8A TO263AB TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	
For Reference Only	Раскаде	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GIB1404-E3/81 Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction 65° C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABPackage-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABOperating Temperature - Junction-65°C ~ 150°C	Manufacturer Part Number	GIB1404-E3/81
Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5 μ A @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5 μ A @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5 μ A @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5 μ A @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Voltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Series	-
Current - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If975mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $975mV @ 8A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $35ns$ Current - Reverse Leakage @ Vr $5\muA @ 200V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Current - Average Rectified (Io)	8A
Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	975mV @ 8A
Current - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Reverse Recovery Time (trr)	35ns
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Current - Reverse Leakage @ Vr	5μA @ 200V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	TO-263AB
Report errors?	Operating Temperature - Junction	-65°C ~ 150°C
Report crois:		Report errors?

GIB1404-E3/81 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GIB1404-E3/81 Payment Methods



GIB1404-E3/81 Shipping Methods



If you have any question about GIB1404-E3/81, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com