

GLM50-24 Information

For Reference Only

Part Number GLM50-24

Manufacturer SL Power Electronics Manufacture of Condor/Ault

Brands

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 50W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GLM50-24 Specifications

| Manufacturer Part Number GLM50-24 Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GLM50 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | | |
|--|--------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GLM50 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Manufacturer Part Number | GLM50-24 |
| Package - Series GLM50 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Manufacturer | SL Power Electronics Manufacture of Condor/Ault Brands |
| Package - Series GLM50 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Category | Power Supplies - External/Internal (Off-Board) |
| Series GLM50 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | | AC DC Converters |
| Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Package | - |
| Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Series | GLM50 |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Type | Open Frame |
| Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Fefficiency Operating Temperature Adjustable Output, Universal Input Mounting Type Size / Dimension 24V Av 24V Av Current - Output (Max) - Chassis Mount 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Number of Outputs | 1 |
| Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation | Voltage - Input | 85 ~ 264 VAC |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation - Efficiency Operating Temperature O°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Carrent - Output (Max) - Output, Universal Input Chassis Mount 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Voltage - Output 1 | 24V |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation | Voltage - Output 2 | - |
| Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Efficiency 85% Operating Temperature O°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 2.1A 2.1A 2.1A 50W Adjustable Voltage - Sow Adjustable Chassis Mount 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Voltage - Output 3 | - |
| Power (Watts) 50W Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Voltage - Output 4 | - |
| Applications Medical Voltage - Isolation - Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Current - Output (Max) | 2.1A |
| Voltage - Isolation Efficiency 85% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Power (Watts) | 50W |
| Efficiency 85% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Applications | Medical |
| Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.25^{\circ}\text{H} (180.0\text{mm} \times 63.5\text{mm} \times 31.8\text{mm})$ | Voltage - Isolation | - |
| Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Efficiency | 85% |
| Mounting Type Chassis Mount Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Operating Temperature | 0°C ~ 50°C |
| Size / Dimension 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) | Features | Adjustable Output, Universal Input |
| | Mounting Type | Chassis Mount |
| Report errors? | Size / Dimension | 4.25" L x 2.50" W x 1.25" H (180.0mm x 63.5mm x 31.8mm) |
| | | Report errors? |

GLM50-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GLM50-24 Payment Methods



















GLM50-24 Shipping Methods













If you have any question about GLM50-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com