

GLM75AG

GLM75AG Information

		Part Number	GLM75AG	
	www.heisenet.com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
		Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
		Description	AC/DC CNVRTR 5.1V +/-12V 12V 75W	
		Package	-	
			For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GLM75AG Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsPackagePower Supplies - External/Internal (Off-Board)Package-SeriesGLM75SpresGLM75Number of Outputs4Voltage - Input90 ~ 264 VACVoltage - Output 15.1VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 45.1XVoltage - Output 45.1XVoltage - Output 5-12VVoltage - Output 6-12VVoltage - Output 78A, 2.5A, 1A, 2.5APower (Watts)-5WApplicationsMedicalVoltage - Soltation-Efficiency78%Operating TemperatureMiguable Output, Universal InputMounting TypeChasis Mount	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GLM75 Type Open Frame Number of Outputs 4 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 12V Voltage - Output 4 5.1X Voltage - Output 5 -25.3 Voltage - Output 6 -25.4 Voltage - Output 7 5.1V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 5.3 Voltage - Solation - Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Cha	Manufacturer Part Number	GLM75AG
AC DC ConvertersPackage-PackageGLM75StriesGDen FrameNumber of Outputs4Voltage - Input90 ~ 264 VACVoltage - Output 10. ~ 264 VACVoltage - Output 212VVoltage - Output 312VVoltage - Output 412VVoltage - Output 412VVoltage - Output 48A, 2.5A, 1A, 2.5AVoltage - Output 45.1WVoltage - Output 475WVoltage - Output 46.1Voltage - Output 475WVoltage - Output 475WVoltage - Soltage76WPower (Wats)-Voltage - Isolation-Voltage - Isolation-Fefficiency76%Operating Temperature6/asis MountMounting TypeChasis MountSize / Dimension7.0° Lx 4.25° W x 1.30° H (177.8m x 108.0mm x 33.0mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesGLM75TypeOpen FrameNumber of Outputs4Voltage - Input90 ~ 264 VACVoltage - Output 15.1VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 48A, 2.5A, 1A, 2.5APower (Wats)75WApplicationsMedicalVoltage - Isolation-Efficiency0°C ~ 50°CFeaturesAjustable Output, Universal InputMounting Type7.0° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series GLM75 Type Open Frame Number of Outputs 4 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 8A, 2.5A, 1A, 2.5A Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature Adjustable Output, Universal Input Mounting Type Chasis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)		AC DC Converters
TypeOpen FrameNumber of Outputs4Voltage - Input90 ~ 264 VACVoltage - Output 15.1VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 48A, 2.5A, 1A, 2.5APower (Watts)75WApplicationsHedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChasis MountSiz / Dimension7.00° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Package	-
Number of Outputs 4 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 5 8A, 2.5A, 1A, 2.5A Power (Wats) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chasis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Series	GLM75
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 12V Voltage - Output 4 5.1X Voltage - Output 4 12V Voltage - Output 4 5.1X Voltage - Output 4 12V Current - Output (Max) 8A, 2.5A, 1A, 2.5A Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dinension 7.00° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Туре	Open Frame
Voltage - Output 1 5.1V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 8A, 2.5A, 1A, 2.5A Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Number of Outputs	4
Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 8A, 2.5A, 1A, 2.5A Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3-12VVoltage - Output 412VCurrent - Output (Max)8A, 2.5A, 1A, 2.5APower (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 1	5.1V
Voltage - Output 412VCurrent - Output (Max)8A, 2.5A, 1A, 2.5APower (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 2	12V
Current - Output (Max)8A, 2.5A, 1A, 2.5APower (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 3	-12V
Power (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 4	12V
ApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Current - Output (Max)	8A, 2.5A, 1A, 2.5A
Voltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Power (Watts)	75W
Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Applications	Medical
Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Isolation	-
FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Efficiency	78%
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Operating Temperature	0° C ~ 50° C
Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)
		Report errors

GLM75AG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GLM75AG Payment Methods



GLM75AG Shipping Methods



If you have any question about GLM75AG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com