

GLM75IG

GLM75IG Information

	Part Number	GLM75IG	
Contraction Com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	<u>ି (ଜ</u> ିକ
	Description	AC/DC CONVERTER 75W	- HE SIL
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GLM75IG Specifications

Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GLM75 Species GLM75 Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Soltofion - Power (Watts) - Voltage - Soltofion - Voltage - Soltofion - Voltage - Soltofion - Efficiency 78% Operating Temperature Ajustable Output, Universal Input Mounting Ty	-			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GLM75 Type Open Frame Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 6 - Voltage - Output 7 - Voltage - Output 8 - Voltage - Output 9 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Solutput 4 - Voltage - Solutput 4 - Voltage - Isolation - Power (Watts) - Voltage - Isolation - Efficiency 78% Operating Temperature Ofc ~ S0°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Si	Manufacturer Part Number	GLM75IG		
AC DC Converters Package - Series GLM75 Type Open Frame Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solution - Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature O°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGLM75TypeOpen FrameNumber of Outputs-Voltage - Input-Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Watts)-Power (Watts)-Voltage - Isolation-Voltage - Isolation-Portuge - Solation-Portuge - Solation-Solatable Output, Universal InputFeaturesAdjustable Output, Universal InputSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GLM75 Type Open Frame Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Wats) - Power (Wats) Medical Voltage - Isolation - Voltage - Isolation - Voltage - Isolation - Voltage - Isolation - Operating Temperature O%C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chasis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)		AC DC Converters		
Type Open Frame Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 4 - Voltage - Soluput 5 - Voltage - Soluput 6 - Power (Watts) - Voltage - Isolation - Voltage - Isolation - Voltage - Isolation - Voltage - Isolation - Voltage - Solupot 7	Package	-		
Number of Outputs-Voltage - Input-Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Current - Output (Max)-Power (Watts)NedicalApplications-Voltage - Isolation-Efficiency78%Operating TemperatureO°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChasis MountSize / Dimension7.00° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Series	GLM75		
Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00°L x 4.25°W x 1.30°H (177.8mm x 108.0mm x 33.0mm)	Туре	Open Frame		
Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Number of Outputs	-		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications Medical Voltage - Isolation - Efficiency 78% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.30° H (177.8mm x 108.0mm x 33.0mm)	Voltage - Input	-		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 1	-		
Voltage - Output 4-Current - Output (Max)-Power (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 2	-		
Current - Output (Max)-Power (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 3	-		
Power (Watts)75WApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Current - Output (Max)	-		
NoVoltage - Isolation-Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Power (Watts)	75W		
Efficiency78%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Applications	Medical		
Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Efficiency	78%		
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Operating Temperature	0° C ~ 50° C		
Size / Dimension 7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)	Features	Adjustable Output, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	7.00" L x 4.25" W x 1.30" H (177.8mm x 108.0mm x 33.0mm)		
		Report errors?		

GLM75IG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GLM75IG Payment Methods Image: Stress of transfer PayPai Image: Stress of transfer Image: Stress of transfer GLM75IG Shipping Methods Image: Stress of transfer <t

If you have any question about GLM75IG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com