

GMC20DRYN-S13

GMC20DRYN-S13 Information

Contact service cases there	 GMC20DRYN-S13 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 40POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GMC20DRYN-S13 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2PitchO.100" (2.54mm)FeaturesGolderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish ThicknessGulContact TypeGulContact TypeSuljin (0.76µm)Contact TypeSuljin (0.76µm)Contact Finish ThicknessSuljin (0.76µm)Contact TypeFull BellowsColorBiackFauge FeatureSuljin (2.54µm)Contact TypeSolderContact Finish ThicknessSolderContact Finish ThicknessSolderContact Finish ThicknessSoljin (0.76µm)Contact TypeFull BellowsContact TypeSolackContact Type	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSolderContact TypeSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Coperating Temperature-65°C ~ 125°C	Manufacturer Part Number	GMC20DRYN-S13
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialOlderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColtact TypeFull BellowsFlange Feature-Coperating Temperature-Operating Temperature-Solver125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessGoldContact TypeFeallewsContact TypeSolderContact TypeSolderContact TypeSolderContact Finish ThicknessSolderContact TypeFeallewsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBackFange Feature-Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish ThicknessGuju (0.76µm)Contact TypeHil BellowsColorBackFange Feature-Operating Temperature50°C ~ 125°C	Series	-
Number of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Gold Contact Type Full Bellows Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	20
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	40
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessSoluin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$
		Report errors?

GMC20DRYN-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GMC20DRYN-S13 Payment Methods



GMC20DRYN-S13 Shipping Methods



If you have any question about GMC20DRYN-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com