

GMM06DTBD-S189

)uote

GMM06DTBD-S189 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GMM06DTBD-S189 Specifications

Manufacturer Part NumberGMM06DTBD-\$189ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeLoop BellowsContact TypeLoop BellowsContact TypeHole, Number DifferenceContact TypeSolderContact TypeSolder <trt< th=""><th></th><th></th></trt<>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type6Contact KinishSolderContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeLoop BellowsColact AppendenceBackFeaturesSolderContact Finish ThicknessSolderContact Finish ThicknesSolderContact Finish ThicknesSolder </td <td>Manufacturer Part Number</td> <td>GMM06DTBD-S189</td>	Manufacturer Part Number	GMM06DTBD-S189
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.9mm)Features-Mounting Type5olderContact MaterialSolderContact FinishGoldContact Finish Thickness0.016 (0.50mm)Contact Finish ThicknessSolin (0.76µm)Contact Finish ThicknessSolin (0.76µm)Contact Finish ThicknessSolin (0.76µm)ColorBackFinage FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact FinishGoldContact Finish ThicknessSolin (0.76µm)Contact TypeHoos PostoneContact Finish ThicknessSolin (0.76µm)Contact Finish ThicknessBiakColorBiackFinage FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish ThicknessJoin (0.76µm)Contact TypeLoop BellowsColorBlackFange FeaturesFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Number of Rows0.156" (3.96mm)Features-Mounting TypeNon Shole KangeYonder AffrictSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessJuji (0.76µm)Contact TypeBackFange FeatureFinish Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type5olderTerminationSolderContact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFange FeaturesFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type1Through Hole, Right AngleContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeaturesFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact FinishGoldContact Finish ThicknessGoldContact TypeLoop BellowsColorBlackFange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	6
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type1Torugh Hole, Right AngleSolderTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	12
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze
Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows
	Color	Black
Operating Temperature $65^{\circ}C$ 125°C	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
operating reinperature -05 C ~ 125 C	Operating Temperature	-65°C ~ 125°C
Report errors?		Report errors?

GMM06DTBD-S189 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GMM06DTBD-S189 Payment Methods





If you have any question about GMM06DTBD-S189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com