

GMM25DRXH

GMM25DRXH Information

Heisener.com	Part Number Manufacturer Category Description Package	GMM25DRXH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 50POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GMM25DRXH Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeSolderContact FinishSolderContact FinishGoldContact Finish ThicknessGuin (0.76µm)Contact TypeFill BellowsContact TypeSolarContact Finish ThicknessSolarContact Finish ThicknessSolarContact TypeFill BellowsContact TypeSolar SolarContact TypeSolar SolarContact TypeSolar SolarContact TypeSolar SolarContact TypeSolar SolarContact TypeSolar SolarContact TypeSolar Solar Sol	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeFinage HoleContact Finish Thickness0.0d2Contact Finish Thickness0.0d2Contact TypeGoldContact TypeGuld In (0.76µm)Contact TypeFil BellowsContact TypeFil BellowsContact TypeGold Contact TypeContact TypeGold Contact TypeContact TypeGold Contact TypeColorBackFlange Feature- Contact Sil (3.18mm) DiaCoperating Temperature- S°C ~ 125°C	Manufacturer Part Number	GMM25DRXH
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Solder0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBackFinage Feature- Sol% C * 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeFul BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange Feature-50°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeGuldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBackFlange Feature-Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-op Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	25
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange Feature-op Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	50
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

GMM25DRXH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GMM25DRXH Payment Methods



GMM25DRXH Shipping Methods



If you have any question about GMM25DRXH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com