




GNT212G Information



Part Number GNT212G

Manufacturer SL Power Electronics Manufacture of Condor/Ault

Brand

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 200W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GNT212G Specifications

Manufacturer Part Number GNT212G Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GNT200 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00° L x 3.00° W x 1.25° H (127.0mm x 76.2mm x 31.8mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GNT200 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Manufacturer Part Number	GNT212G	
Package - Series GNT200 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
Package - Series GNT200 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series GNT200 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)		AC DC Converters	
TypeOpen FrameNumber of Outputs1Voltage - Input100 ~ 240 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)200WApplicationsITE (Commercial)Voltage - Isolation-Efficiency90%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Package	-	
Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 100 ~ 240 VAC 12V 12V 12V 12V 12V 12V 12V 12	Series	GNT200	
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 12.5A - Current - Output (Max) 12.5A - Current - Outp	Туре	Open Frame	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Voltage - Isolation Fefficiency Operating Temperature Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Size / Dimension - Coutput 2 - - Commercial - Comme	Voltage - Input	100 ~ 240 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Councided the sense of the	Voltage - Output 1	12V	
Voltage - Output 4 Current - Output (Max) 12.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Voltage - Output 2	-	
Current - Output (Max) 12.5A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Current - Output (Max)	12.5A	
Voltage - Isolation - Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Power (Watts)	200W	
Efficiency 90% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Applications	ITE (Commercial)	
Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Voltage - Isolation	-	
Features Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Efficiency	90%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	
Size / Dimension 5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	Features	Adjustable Output, PFC, Remote Sense, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.25" H (127.0mm x 76.2mm x 31.8mm)	
*			Report errors?

GNT212G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GNT212G Payment Methods





















GNT212G Shipping Methods













If you have any question about GNT212G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com