



GP10D-E3/73 Information

www.helsaner.com

For Reference Only

Part Number GP10D-E3/73

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 200V 1A DO204AL

Package DO-204AL, DO-41, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GP10D-E3/73 Specifications

Manufacturer Part NumberGP10D-E3/73ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-204AL, DO-41, AxialSeriesSUPERECTIFIER?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.1V @ 1ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-204AL, DO-41, AxialSeriesSUPERECTIFIER?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.1V @ 1ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	GP10D-E3/73
Diodes - Rectifiers - SinglePackageDO-204AL, DO-41, AxialSeriesSUPERECTIFIER?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.1V @ 1ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageDO-204AL, DO-41, AxialSeriesSUPERECTIFIER?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.1V @ 1ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
Series SUPERECTIFIER? Diode Type Standard Voltage - DC Reverse (Vr) (Max) 200V Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 1.1V @ 1A Speed Standard Recovery >500ns, > 200mA (Io) Reverse Recovery Time (trr) 3µs Current - Reverse Leakage @ Vr 5µA @ 200V Capacitance @ Vr, F 8pF @ 4V, 1MHz Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction -65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.1V @ 1ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C	Package	DO-204AL, DO-41, Axial
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.1V @ 1A Speed Standard Recovery >500ns, > 200mA (Io) Reverse Recovery Time (trr) 3µs Current - Reverse Leakage @ Vr 5µA @ 200V Capacitance @ Vr, F 8pF @ 4V, 1MHz Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction 200V	Series	SUPERECTIFIER?
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Standard Recovery >500ns, > 200mA (Io) Reverse Recovery Time (trr) Supacitance @ Vr, F Mounting Type Package / Case Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction 1.1V @ 1A 1.1V @ 1A 1.1V @ 1A Standard Recovery >500ns, > 200mA (Io) Supacitance (Io) Supacitance (Io) Supacitance (Io) 1.1V @ 1A 1.1V @	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Standard Recovery >500ns, > 200mA (Io) Reverse Recovery Time (trr) 3μs Current - Reverse Leakage @ Vr Capacitance @ Vr, F 8pF @ 4V, 1MHz Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction	Voltage - DC Reverse (Vr) (Max)	200V
SpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)3μsCurrent - Reverse Leakage @ Vr5μA @ 200VCapacitance @ Vr, F8pF @ 4V, 1MHzMounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-204AL (DO-41)Operating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	1A
Reverse Recovery Time (trr) $3\mu s$ Current - Reverse Leakage @ Vr $5\mu A$ @ $200V$ Capacitance @ Vr, F $8pF$ @ $4V$, $1MHz$ Mounting Type $Through$ Hole Package / Case $DO-204AL$, $DO-41$, $Axial$ Supplier Device Package $DO-204AL$ ($DO-41$) Operating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$	Voltage - Forward (Vf) (Max) @ If	1.1V @ 1A
Current - Reverse Leakage @ Vr $5\mu A$ @ $200V$ Capacitance @ Vr, F $8pF$ @ $4V$, $1MHz$ Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) $-65^{\circ}C \sim 175^{\circ}C$	Speed	Standard Recovery >500ns, > 200mA (Io)
Capacitance @ Vr, F 8pF @ 4V, 1MHz Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction -65°C ~ 175°C	Reverse Recovery Time (trr)	3μs
Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction Through Hole DO-204AL, DO-41, Axial -65°C ~ 175°C	Current - Reverse Leakage @ Vr	5μA @ 200V
Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction -65°C ~ 175°C	Capacitance @ Vr, F	8pF @ 4V, 1MHz
Supplier Device Package DO-204AL (DO-41) Operating Temperature - Junction -65°C ~ 175°C	Mounting Type	Through Hole
Operating Temperature - Junction -65°C ~ 175°C	Package / Case	DO-204AL, DO-41, Axial
	Supplier Device Package	DO-204AL (DO-41)
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

GP10D-E3/73 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GP10D-E3/73 Payment Methods



















GP10D-E3/73 Shipping Methods













If you have any question about GP10D-E3/73, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com