



GP2M005A060HG Information



For Reference Only

Part Number GP2M005A060HG

ManufacturerGlobal Power Technologies GroupCategoryDiscrete Semiconductor Products
Transistors - FETs, MOSFETs - Single

Description MOSFET N-CH 600V 4.2A TO220

Package TO-220-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GP2M005A060HG Specifications

Manufacturer Part Number GP2M005A060HG Manufacturer Global Power Technologies Group Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package TO-220-3 Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 600V Current - Continuous Drain (Id) @ 25°C 4.2A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250µA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3		
Category Discrete Semiconductor Products Transistors - FETs, MOSFETs - Single Package TO-220-3 Series - FET Type N-Channel Technology MOSFET (Metal Oxide) foot four - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds Vgs (Max) FET Feature Power Dissipation (Max) Rds On (Max) @ Id, Vgs Qhay Perating Temperature -55°C ~ 150°C (TJ) Mounting Type Supplier Device Package Package / Case TO-220 Package / Case	Manufacturer Part Number	GP2M005A060HG
Package TO-220-3 Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 600V Current - Continuous Drain (Id) @ 25°C 4.2A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250μA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Manufacturer	Global Power Technologies Group
Package TO-220-3 Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 600V Current - Continuous Drain (Id) @ 25°C 4.2A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250μA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Category	Discrete Semiconductor Products
Series - FET Type N-Channel Technology MOSFET (Metal Oxide) Drain to Source Voltage (Vdss) 600V Current - Continuous Drain (Id) @ 25°C 4.2A (Tc) Drive Voltage (Max Rds On, Min Rds On) 10V Vgs(th) (Max) @ Id 5V @ 250μA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3		Transistors - FETs, MOSFETs - Single
FET TypeN-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)600VCurrent - Continuous Drain (Id) @ 25°C4.2A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μAGate Charge (Qg) (Max) @ Vgs14nC @ 10VInput Capacitance (Ciss) (Max) @ Vds658pF @ 25VVgs (Max)±30VFET Feature-Power Dissipation (Max)98.4W (Tc)Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	Package	TO-220-3
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)600VCurrent - Continuous Drain (Id) @ 25°C4.2A (Tc)Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μAGate Charge (Qg) (Max) @ Vgs14nC @ 10VInput Capacitance (Ciss) (Max) @ Vds658pF @ 25VVgs (Max)±30VFET Feature-Power Dissipation (Max)98.4W (Tc)Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	Series	-
Drain to Source Voltage (Vdss)600 VCurrent - Continuous Drain (Id) @ 25°C4.2A (Tc)Drive Voltage (Max Rds On, Min Rds On)10 VVgs(th) (Max) @ Id5 V @ 250μAGate Charge (Qg) (Max) @ Vgs14nC @ 10 VInput Capacitance (Ciss) (Max) @ Vds658pF @ 25 VVgs (Max)±30 VFET Feature-Power Dissipation (Max)98.4W (Tc)Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10 VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	FET Type	N-Channel
Current - Continuous Drain (Id) @ 25°C Drive Voltage (Max Rds On, Min Rds On) Vgs(th) (Max) @ Id Sty @ 250μA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature Mounting Type Through Hole Supplier Device Package Package / Case TO-220-3	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)10VVgs(th) (Max) @ Id5V @ 250μAGate Charge (Qg) (Max) @ Vgs14nC @ 10VInput Capacitance (Ciss) (Max) @ Vds658pF @ 25VVgs (Max)±30VFET Feature-Power Dissipation (Max)98.4W (Tc)Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	Drain to Source Voltage (Vdss)	600V
Vgs(th) (Max) @ Id 5V @ 250μA Gate Charge (Qg) (Max) @ Vgs 14nC @ 10V Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Current - Continuous Drain (Id) @ 25°C	4.2A (Tc)
Gate Charge (Qg) (Max) @ Vgs Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) ±30V FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Drive Voltage (Max Rds On, Min Rds On)	10V
Input Capacitance (Ciss) (Max) @ Vds 658pF @ 25V Vgs (Max) FET Feature - Power Dissipation (Max) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Vgs(th) (Max) @ Id	5V @ 250μA
Vgs (Max)±30VFET Feature-Power Dissipation (Max)98.4W (Tc)Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	Gate Charge (Qg) (Max) @ Vgs	14nC @ 10V
FET Feature - Power Dissipation (Max) 98.4W (Tc) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Input Capacitance (Ciss) (Max) @ Vds	658pF @ 25V
Power Dissipation (Max) Rds On (Max) @ Id, Vgs 2.1 Ohm @ 2.1A, 10V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Vgs (Max)	±30V
Rds On (Max) @ Id, Vgs2.1 Ohm @ 2.1A, 10VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HoleSupplier Device PackageTO-220Package / CaseTO-220-3	FET Feature	-
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Power Dissipation (Max)	98.4W (Tc)
Mounting Type Through Hole Supplier Device Package TO-220 Package / Case TO-220-3	Rds On (Max) @ Id, Vgs	2.1 Ohm @ 2.1A, 10V
Supplier Device Package TO-220 Package / Case TO-220-3	Operating Temperature	-55°C ~ 150°C (TJ)
Package / Case TO-220-3	Mounting Type	Through Hole
	Supplier Device Package	TO-220
Report errors?	Package / Case	TO-220-3
		Report errors?

GP2M005A060HG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GP2M005A060HG Payment Methods

































If you have any question about GP2M005A060HG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com