

GPC80D

GPC80D Information

	Part Number	GPC80D	
	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	9172 4
	Description	AC/DC CNVRTR 5V 24V -12V 12V 80W	k 8.3 72
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quot

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPC80D Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-PackageGPC80StriesGPC80Number of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 412VCurrent - Output (Max)SOW (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Current - Output form90% (100W Forced Air)Power (Watts)0%Applications-Applications-Operating Temperature0% C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChasis MountSize / Dimension7,00° L x 4.25° W x 1.86° H (177.8m x 108.0mm x 47.2mm)	•			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GPC80 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Solation - Power (Watts) 80W (110W Forced Air) Applications - Voltage - Isolation - Efficiency 0% Operating Temperature 0°C ~ 5°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size /	Manufacturer Part Number	GPC80D		
AC DC Converters Package - Series GPC80 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 5 80W (110W Forced Air) Power (Watts) ABW (110W Forced Air) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.0°L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPC80TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 480W (110W Forced Air)Power (Watts)S0W (110W Forced Air)Applications-Efficiency0%Operating Temperature0%Poutput 50%Augustable Output 40%States30% (110W Forced Air)States0%Operating Temperature0%StatesAigustable Output, Remote Sense, Universal InputMounting TypeChasis MountSiz / Dimension7.0" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GPC80 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 12A, 2A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature Adjustable Output, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)		AC DC Converters		
TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 412APower (Wats)80W (110W Forced Air)Power (Wats)-Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Package	-		
Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 12V Current - Output (Max) 12A, 2A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Series	GPC80		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 12A, 2A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications TTE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Туре	Open Frame		
Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 12A, 2A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 0°C ~ 50°C (With Derating) Peatures Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.0°'L x 4.25'' W x 1.86'' H (177.8mm x 108.0mm x 47.2mm)	Number of Outputs	4		
Voltage - Output 2 24V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 12A, 2A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-12VVoltage - Output 412VCurrent - Output (Max)12A, 2A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 1	5V		
Voltage - Output 412VCurrent - Output (Max)12A, 2A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 2	24V		
Current - Output (Max)12A, 2A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 3	-12V		
Power (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 4	12V		
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Current - Output (Max)	12A, 2A, 1A, 1A		
Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Power (Watts)	80W (110W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Efficiency	70%		
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Operating Temperature	0° C ~ 50° C (With Derating)		
Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Features	Adjustable Output, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Descent server 2	Size / Dimension	7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)		
Report errors?		Report errors?		

GPC80D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about GPC80D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com